

YD580 机型尺寸及重量

YD580T4-0P7G/1P5PB ~ YD580T4-160G/200P 外形/安装孔位尺寸及重量

框号	变频器型号	外形尺寸 mm				安装孔位 mm		安装 孔径 mm	重量 kg
		W	H	H1	D	A	B	d1	
F1	YD580T4-0P7G/1P5PB	123	200	/	172	119.4	189.4	φ5	2
	YD580T4-1P5G/2P2B								
	YD580T4-2P2G/3P0PB								
	YD580T4-3P0G/3P7PB								
	YD580T4-3P7G/5P5PB								
	YD580T4-5P5G/7P5PB								
F2	YD580T4-7P5G/11PB	140	250	/	178	129	239	φ6	3.3
	YD580T4-11G/15PB								
F3	YD580T4-15G/18P5PB	180	280	/	180	165.4	266.7	φ6	4.3
F4	YD580T4-18P5G/22PB	225	360	/	235	206	341	Φ7	9.1
	YD580T4-22G/30PB								
F5	YD580T4-30G/37P(B)	255	436	422	239	213	421	φ7	17.5
	YD580T4-37G/45P(B)								
F6	YD580T4-45G/55P(B)	302	540	527	285	245	522	φ10	35
	YD580T4-55G/75P(B)								
F7	YD580T4-75G/90P(B)	340	581	560	316	270	558	φ10	51.5
	YD580T4-90G/110P								
	YD580T4-110G/132P								
F8	YD580T4-132G/160P	400	925	885	322	320	905	φ10	85
	YD580T4-160G/200P								

YD580T4-200G/220P ~ YD580T4-450G/500P 外形/安装孔位尺寸及重量 (无输出电抗器)

框号	变频器型号	外形尺寸 mm					安装孔位 mm				安装 孔径 mm	重量 kg
		W	W1	H	H1	D	A1	A2	B1	B2	d1	
F9	YD580T4-200G/220P	302	364	1136	1091	507	240	150	1035	83	φ13	110
	YD580T4-220G/250P											
F10	YD580T4-250G/280P	333	396	1286	1245	552	225	185	1175	91	φ13	155
	YD580T4-280G/315P											
F11	YD580T4-315G/355P	345	402	1404	1355	545	240	185	1291	91	φ16	185
	YD580T4-355G/400P											
	YD580T4-400G/450P											
	YD580T4-450G/500P											

YD580T4-200G/220P ~ YD580T4-450G/500P 外形/安装孔位尺寸及重量 (含输出电抗器)

框号	变频器型号	外形尺寸 mm					安装孔位 mm				安装 孔径 mm	重量 kg
		W	W1	H	H1	D	A1	A2	B1	B2	d1	
F9 -L	YD580T4-200G/220P-L	302	364	1474	1429	507	240	150	1035	421	φ13	160
	YD580T4-220G/250P-L											
F10 -L	YD580T4-250G/280P-L	333	396	1624	1583	552	225	185	1175	429	φ13	215
	YD580T4-280G/315P-L											
F11 -L	YD580T4-315G/355P-L	345	402	1732	1683	545	240	185	1291	419	φ16	245
	YD580T4-355G/400P-L											
	YD580T4-400G/450P-L											
	YD580T4-450G/500P-L											